

SMART LFP POWER, ENGINEERED FOR THE NORTH

Naali

ACB26

12.8 V / 210 Ah / 2.6 kWh

A mid-capacity smart LFP platform for mobile, marine and off-grid systems needing more runtime than the entry model, with the same intelligent protection and connectivity.



SMART HEATING

CAN BUS

BLUETOOTH

ACTIVE BALANCE

BUILT FOR DEMANDING ENERGY SYSTEMS

Power that communicates.

Naali combines A-grade LiFePO_4 cells with an AbyssCore smart BMS, active balancing and application-level connectivity. Monitor battery health in detail, integrate with supported energy systems and keep critical loads protected.

100 A

CONTINUOUS DISCHARGE

200 A

30-SECOND PULSE

>3,500

CYCLES TO 80% SOH

20 kg

BATTERY WEIGHT

01 Arctic adaptability

Integrated smart heating and temperature-aware BMS protection support demanding cold-climate installations.

02 Connected by design

CAN bus and Bluetooth enable system integration, setup, firmware updates and mobile monitoring.

03 Granular telemetry

Track voltage, current, temperatures, SOC, SOH, energy, capacity, cell values and error states.

04 Application-ready

Adaptable enclosure and connectivity options support mobile, marine, solar and specialist OEM projects.

TECHNICAL DATA

Naali / ACB26

12.8 V smart LiFePO₄ battery with integrated heating, active balancing and connected battery management.

Nominal voltage	12.80 V	Maximum voltage	14.65 V
Minimum voltage	10.00 V	Nominal capacity	210 Ah / 2.6 kWh
Continuous discharge	100 A	Pulse discharge	200 A / 30 s
Maximum charge	105 A (50 A recommended)	Balancing current	2 A
Discharge temperature	-20 to +55 °C	Charge temperature	0 to +55 °C
Heating system	Active, cold-start	Cell chemistry	LiFePO ₄ , A-grade
Dimensions (W×H×D)	276×195×248 mm	Weight	20 kg
Communication	CAN bus (NMEA2000) / Bluetooth	Integration	Victron and compatible systems

SMART BMS VISIBILITY

Know what the battery is doing.

- Pack and individual cell voltage
- Current and operating state
- Cell and power-stage temperatures
- State of charge and state of health
- Energy, remaining capacity and errors

DESIGNED TO INTEGRATE

Built for the complete system.

- Mobile and recreational vehicles
- Marine auxiliary energy
- Solar and off-grid storage
- Specialist rescue and field equipment
- Custom OEM and infrastructure projects

FIELD-PROVEN CUSTOMER RESULT

The Naali 2.6 kWh platform delivers double the capacity of the entry model in a still-compact enclosure — built for installations that have outgrown a single small battery but do not yet need a full house energy storage system.

SUOMEN AKKUTALO OY

Product information: Specifications are based on document ACB26 v1.0 / 2026-09. Product configuration and integration requirements may vary by application. Verify the final specification, charging design, protection, certification and installation requirements before ordering or installation. CE status is stated for the cells and BMS in the supplied product information. Information is subject to change without notice.